

Instructions for #1025500

Fits full-size 1994-2001 Dodge V6 & V8 pickups with 2.5" exhaust at converter

Note: do not tighten any clamps until the last step!

1) remove the spare tire from under the truck. Because of clearance problems, you will not be able to run this system with the spare tire in its original position. Therefore, it must be pulled permanently!!!

2) remove exhaust system leaving only the original y pipe, o.e. rubber hanger mounts, and catalytic converter on the truck.

Note: the extension pipe will fit the longer wheel base trucks without cutting. On all other vehicles the extension pipe will need to be cut from the **3" o.d.** end (the end that is not shrunk) as necessary.

3) slip the front pipe into place. With the tail pipes in the rear of the muffler, hold up the muffler and tail pipes in a position that clears all chassis components. Mark the front pipe. Make sure to account for at least 2" of the pipe to go into the muffler. Cut the front pipe.

4) use a 2-1/2" clamp to attach the extension pipe to the catalytic converter.

5) use a 3" clamp to attach the muffler (#6842 or equivalent) to the extension pipe.

6) slip the right and left over the axle pipes into the muffler. Both tail pipes are routed between the shock and where the spare tire was.

7) with the muffler and over the axle pipes in place, install the two thu900 hangers above the outlets of the muffler to the frame. Note: it may be necessary to drill 5/16" holes in the frame if no holes are present. Use 5/16" x 1" bolts, nuts, lock washers, and fender washers to connect the hangers to the frame.

8) mount the muffler and tail pipes to the hangers using the 3" clamps (one for each outlet of the muffler).

9) install the 28" long 3" i.d./o.d. tail pipe extensions to the over the axle pipes.

10) locate mounting holes in the frame near the end of the over the axle sections of the tail pipes. If no mounting holes are present, drill a 5/16" hole in the frame for each tail pipe. Install the remaining thu900 hangers using the fender washers, nuts, bolts and lock washers. Clamp the hangers to the rear tail pipe extensions, connecting the two pipes and the hangers.

11) trim tail pipes to your desired lengths.

12) tighten all clamps and nuts and bolts and check for clearance of brake lines and chassis components.

Hardware

- | | |
|---------------------------------|-------------------------------------|
| 1) 2.50" clamp | 1) front extension pipe # 1025500-3 |
| 5) 3" clamp | 1) left tail pipe # 1028350-2 |
| 4) 5/16" lock washers | 1) right tail pipe # 1028350-1 |
| 4) 5/16" x 1" bolts | 1) 6842 muffler |
| 4) 5/16" nuts | 2) tail pipe extensions |
| 4) fender washers | |
| 4) thu900 (360 swinger)—br91930 | |

Danger warning: should the purchaser decide to install this, or any other exhaust product at home, be warned that pleasure car or light duty truck/van "bumper jacks" are intended for emergency use only. The use of frame contact jack stands in conjunction with a floor jack as main support is highly recommended to minimize accidental dropping of a vehicle while the installation proceeds.


Notes:

- the left tail pipe has 6 bends--the inlet is the long end
- the right tail pipe has 5 bends--the inlet is the short end
- the muffler outlets should both be parallel to the ground and run side by side
- we recommend use of a drive-on lift for installation. Use of a frame contact hoist (one that lifts the vehicle in which the rear axle drops below ride height) will make the installation more difficult
- both tail pipes are routed between the shock and where the spare tire was

Instructions for 1025500



FOR DETAILED DIGITAL PICTURES OF THIS SYSTEM INSTALLED EMAIL US AT
mike@heartthrobexhaust.com www.heartthrobexhaust.com 320-693-0222



BUILD SHEET FOR: 3” Cat-Back Dual Kit

PART: 1025500

- _____ 1) #6842 MUFFLER
- _____ 1) LEFT TAIL PIPE—1028350-2
- _____ 1) RIGHT TAIL PIPE—1028350-1
- _____ 2) LEFT & RIGHT TAIL PIPE Extensions
- _____ 1) FRONT EXTENSION PIPE—1025500-3
- _____ 1) HARDWARE KIT

INSPECTED BY: _____

DATE: _____

INSPECTED BY: _____

DATE: _____

BUILD SHEET FOR: 3” Cat-Back Dual Kit

PART: 1025500

- _____ 1) #6842 MUFFLER
- _____ 1) LEFT TAIL PIPE—1028350-2
- _____ 1) RIGHT TAIL PIPE—1028350-1
- _____ 2) LEFT & RIGHT TAIL PIPE Extensions
- _____ 1) FRONT EXTENSION PIPE—1025500-3
- _____ 1) HARDWARE KIT

INSPECTED BY: _____

DATE: _____

INSPECTED BY: _____

DATE: _____